


NOTICE - APR Series Part Number Change



www.tpcpage.com

Before



1 RODLESS CYLINDER Series

2 Bore size

- 16 : 16mm
- 20 : 20mm
- 25 : 25mm
- 32 : 32mm
- 40 : 40mm
- 50 : 50mm
- 63 : 63mm

3 Guide type

- A : Standard
- B : External guide type
- C : LM guide type
(not available with $\varnothing 50, 63$)

4 Stroke(mm)

- A, B Type / C Type
- $\varnothing 16$: 3,000 / 1,000
- $\varnothing 20$: 3,000 / 1,000
- $\varnothing 25$: 5,000 / 1,000
- $\varnothing 32$: 5,000 / 1,000
- $\varnothing 40$: 5,000 / 2,000
- $\varnothing 50$: 5,000 / -
- $\varnothing 63$: 5,000 / -
- ※ Contact us for longer than max. stroke

5-1 Stroke adjustment unit (1)

- Blank : None
- B1 : Shock absorber (single)
- B2 : Shock absorber (both)
(only available with "A" type up to $\varnothing 40$)

5-2 Stroke adjustment unit (2)

- Please refer to the table on p.***
- ※ Unit (1) and (2) can't be applied together

6 Option (1)

- Blank : None
- SA : Side bracket A type
- SB : Side bracket B type
(not applicable with LM guide type)

→ Additional symbol

- Blank : 1 Set (2EA)
- N : n Sets

7 Option (2)

- Blank : None
- J : Floating bracket
(only applicable with A type)


8 Auto switch

- Blank : None
- W8H : Micro auto switch
(DC24V, AC110V)
- W9H : Micro auto switch
(DC24V)

→ Additional symbol

- Blank : 2pcs
- N : n pcs

After



1 RODLESS CYLINDER Series

2 Guide type

- A: Standard
- B: External guide type
- C: LM guide type
(not available with $\varnothing 50, 63$)

3 Bore size

- 16 : 16mm
- 20 : 20mm
- 25 : 25mm
- 32 : 32mm
- 40 : 40mm
- 50 : 50mm
- 63 : 63mm

4 Stroke(mm)

- A, B Type / C Type
- $\varnothing 16$: 3,000 / 1,000
- $\varnothing 20$: 3,000 / 1,000
- $\varnothing 25$: 5,000 / 1,000
- $\varnothing 32$: 5,000 / 1,000
- $\varnothing 40$: 5,000 / 2,000
- $\varnothing 50$: 5,000 / -
- $\varnothing 63$: 5,000 / -
- ※ Contact us for longer than max. stroke

5-1 Stroke adjustment unit (1)

- Blank : None
- B1 : Shock absorber (single)
- B2 : Shock absorber (both)
(only available with "A" type up to $\varnothing 40$)

5-2 Stroke adjustment unit (2)

- Please refer to the table on p.***
- ※ Unit (1) and (2) can't be applied together

6 Option (1)

- Blank : None
- SA : Side bracket A type
- SB : Side bracket B type
(not applicable with LM guide type)

→ Additional symbol

- Blank : 1 Set (2EA)
- N : n Sets

7 Option (2)

- Blank : None
- J : Floating bracket
(only applicable with A type)

8 Auto switch

- Blank : None
- W8H : Micro auto switch
(DC24V, AC110V)
- W9H : Micro auto switch
(DC24V)

→ Additional symbol

- Blank : 2pcs
- N : n pcs

※ Except guide type, bore size, all options will remain same as before.