


Notice - ARD Series Part Number Change




www.tpcpage.com

Before



- | | | |
|--|---|---|
| <p>1 Round cylinder ※ Built-in magnet, bumper, and non-lube type is standard</p> <p>2 Mounting B : Standard</p> <p>3 Cushion Blank : Rubber (standard) A : Air cushion</p> <p>4 Bore 20 : Ø20mm 25 : Ø25mm 32 : Ø32mm 40 : Ø40mm 50 : Ø50mm 63 : Ø63mm ※ Contact us for 80, 100, and 125</p> | <p>5 Stroke(mm) * Rubber cushion Ø20 : 25~350mm Ø25 : 25~400mm Ø32 : 25~450mm Ø40 : 25~800mm Ø50 : 25~1,200mm Ø63 : 25~1,200mm * Air cushion Ø20 : 25~350mm Ø25 : 25~400mm Ø32 : 25~450mm Ø40 : 25~800mm Ø50 : 25~1,200mm Ø63 : 25~1,200mm</p> | <p>6 Auto switch W5 : W5 reed switch (0.5m lead wire) ※ Please add L for 3m lead wire ex) W5L</p> <p>7 Number of switches Blank : 2 pcs S : 1pc n : n pcs</p> |
|--|---|---|

After



- | | | |
|---|---|---|
| <p>1 Round cylinder ※ Built-in magnet, bumper, and non-lube type is standard</p> <p>2 Mounting B : Standard L : Foot F : Rod side flange G : Head side flange D : Double clevis</p> <p>3 Bore size 20 : Ø20mm 25 : Ø25mm 32 : Ø32mm 40 : Ø40mm 50 : Ø50mm 63 : Ø63mm ※ Contact us for 80, 100, and 125</p> | <p>4 Stroke(mm) * Rubber cushion Ø20 : 25~350mm Ø25 : 25~400mm Ø32 : 25~450mm Ø40 : 25~800mm Ø50 : 25~1,200mm Ø63 : 25~1,200mm * Air cushion Ø20 : 25~350mm Ø25 : 25~400mm Ø32 : 25~450mm Ø40 : 25~800mm Ø50 : 25~1,200mm Ø63 : 25~1,200mm</p> <p>5 Cushion Blank : Rubber (standard) A : Air cushion</p> | <p>6 Rod end shape Blank : Male thread F : Female thread</p> <p>7 Auto switch W5 : W5 reed switch (0.5m lead wire) ※ Please add L for 3m lead wire ex) W5L</p> <p>8 Number of switches Blank : 2 pcs S : 1pc n : n pcs</p> |
|---|---|---|

※ Except mounting, cushion, and rod end shape, all options will remain same as before.